



factory certificate



product:	cord end-sleeves, insulated on tape
surface:	tin plated: 3 - 5 µm
insulation:	polypropylene (heat resistant up to 110°C)
art-number:	A 28003.. – A 28403..
norm:	DIN colour-code
material:	Cu-ETP acc. to EN 13600
information:	RoHS-conform (EU-Direktive 2002/95/EC)

Eisenacher
quality management





Cord end-sleeves

mm ²		DIN		ordercode	AWG	nominal size	dimensions					
		colour-code	art-number				l1	l2	d1	s1	d2	s2
0,5	N	white	A 28003	..	20,0	0,50 - 8	14,0	8,0	1,0	0,20	2,8	3,5
0,75	N	grey	A 28103	..	18,0	0,75 - 8	14,0	8,0	1,2	0,20	2,8	3,5
1,00	N	red	A 28203	..	17,0	1,00 - 8	14,0	8,0	1,4	0,20	3,3	4,0
1,50	N	black	A 28303	..	15,0	1,50 - 8	14,0	8,0	1,7	0,20	3,3	4,0
2,50	N	blue	A 28403	..	13,0	2,50 - 8	14,0	8,0	2,2	0,20	4,2	4,0
		Version			D = Ø		nominal size		VE			
		Strips		0			0,5 - 2,50 mm ²		10x50			
		PE-spool		1	145 mm		0,5 - 0,75 mm ²		1.100			
				1			1,0 - 1,50 mm ²		800			
				1			2,50 - 2,50 mm ²		500			
		Small-spool (cardboard)		2	250 mm		0,5 - 1,00 mm ²		3.000			
				2			1,50 mm ²		2.500			
		Middle-spool (cardboard)		5	320 mm		0,5 - 1,50 mm ²		5.000			
				5			2,50 mm ²		3.000			
		Large-spool (cardboard)		3	610 mm		0,50 - 0,75 mm ²		10.000			
				3			1,0 - 1,50 mm ²		7.500			
				3			2,50 mm ²		5.000			
		Box (150x150mm)		4			0,5 - 1,50mm ²		1.000			
				4			2,50mm ²		500			

