


factory certificate



product: female disconnects
art-number: F 5012800.. .. – F 5049500.. ..
norm: DIN 46247, DIN 46330 part 2 and similar
surface:
- bare
- tin plated: 3 - 5 µm
- fire tin plated: 3 - 5 µm
- nickel plated: 3 µm
- silver plated: 0,5 µm
material: brass, bronze, tin zinc-bronze, steel
information: RoHS-conform (EU-Direktive 2002/95/EC)

Eisenacher
quality management





female disconnects

mm ²	AWG	nominal size	art-number	order code	tab-width	tab-thickness	dimensions		~kg 1000 St.	VE
							l1	l2		
0,1 – 0,25	20	2,8 – 0,25	F 5012800	2,8	0,8	14,0	6,3	0,20	1.000
0,5 – 1,50	17	2,8 – 1,00	F 5022800	2,8	0,5	12,5	5,0	0,25	1.000
			F 5022810	2,8	0,5	14,0	6,3	0,24	1.000
			F 5022820	2,8	0,8	12,5	5,0	0,23	1.000
			F 5022830	2,8	0,8	14,0	6,3	0,25	1.000
		4,8 – 1,00	F 5024800	4,8	0,5	15,6	6,0	0,50	1.000
			F 5024810	4,8	0,8	15,6	6,0	0,50	1.000
1,5 – 2,50	13	4,8 – 2,50	F 5034800	4,8	0,5	15,6	6,0	0,54	1.000
			F 5034810	4,8	0,8	15,6	6,0	0,54	1.000
		6,3 – 2,50	F 5036300	6,3	0,8	19,0	7,4	0,92	1.000
2,5 – 6,00	10	6,3 – 6,00	F 5046300	6,3	0,8	19,0	7,4	0,98	1.000
		9,5 – 6,00	F 5049500	9,5	1,2	24,5	12,0	1,50	1.000
material				surface						
brass				1	1	bare				
bronze				2	2	tin plated				
tin-zinc bronze				3	3	fire tin plated				
steel				4	4	nickel plated				
					5	silver plated				